



## SPECIFICATIONS

## KIOSK SCAN

### IMAGING



Active Scan Area	125 mm × 55 mm (4.92" × 2.17")
Illumination Sources	LED visible white, IR (B900)
Image Resolution	500 PPI
Provided Images	Visible, IR, OVD image, glare-free image
Image Formats	BMP, JPG, JPG2000 and PNG
Image Color Depth	24 bits/pixels [RGB, 8 bits/pixels (IR image)]

### READING CAPABILITY

Automatic Document Detection (ADD)	YES
Reflection Removal (RR)	YES
ICAO MRZ Reading	ICAO compliant documents per ICAO 9303 specification Part 1, Part 1 <sub>v2</sub> , Part 2, Part 3 and Part 3 <sub>v2</sub> for Type ID-1, ID-2 and ID-3 MRZ Optical Character Recognition
VIZ Reading	Available, based on user-defined fields
Barcode Reading	1D: UPC-A, EAN8, EAN13, Code39, Code128 and ITF 2D: PDF 417, Data Matrix, QR Code, Aztec Code From paper based documents and mobile devices AAMVA compliant PDF417 and IATA BCBP

### PROGRAMMING & INTERFACES

Supported Operation Systems	Windows 8.1, 8, 7, Vista (32/64 bit, WHQL certified) 32/64 bit Server 2008 R2 and Server 2003 Linux Ubuntu, Debian, OpenSUSE, CentOS
Software Development Kit (SDK)	Complete SDK including DLLs and demo programs
Programming Languages	C/C++, C#, Visual Basic 6.0, Delphi, VB.NET, Java
General Interfaces	ARH native, Twain and Micros Opera™
Advanced Document Authentication Module	Data consistency checks: MRZ vs. VIZ vs. Bar codes IR B900 check
PC Connection	USB 2.0 high speed
Internal Memory	Storing factory calibration
Firmware Upgrade	Automatic, via USB



### MECHANICAL AND OTHER DATA

Size (width × depth × height)	125 mm × 123 mm × 58.5 mm (4.92" × 4.84" × 2.3")
Weight	0.6 kg (1.32 lbs.)
Operating Temperature	5 °C - 45 °C (45 °F - 113 °F)
Operating Humidity	0-95 % (non-condensing)
Power supply	From USB, no external power supply is required
IP rate	IP53
Case	Metal case
Window glass	4 mm tempered glass
Compliances	FCC, CE, WEEE, RoHS
Maintenance	No moving parts, maintenance-free operation
Warranty	12 months warranty, upgradeable

